

CLAIMS

1. A magnetorheological damper comprising:

a) an inner tube;

b) a magnetorheological piston disposed within and slideably engaging the inner tube; and

5 c) an outer tube surrounding the inner tube, wherein the outer tube is in fluid communication with the inner tube.

2. The magnetorheological damper of claim 1, wherein the inner tube has a first end and has a second end, and wherein the outer tube is in fluid communication with the inner tube proximate the first end of the inner tube.

3. The magnetorheological damper of claim 2, also including a valve disposed proximate the first end of the inner tube and providing the fluid communication of the outer tube with the inner tube.

4. The magnetorheological damper of claim 3, also including a rod having a first end attached to the magnetorheological piston and having a second end extending outside the inner and outer tubes, wherein the second end of the inner tube is disposed between the first end of the inner tube and the
5 second end of the rod, and wherein the rod contains an electrode operatively connected to the magnetorheological piston.

5. The magnetorheological damper of claim 2, also including a rod having a first end attached to the magnetorheological piston and having a second end extending outside the inner and outer tubes, wherein the second end of the inner tube is disposed between the first end of the inner tube and the
5 second end of the rod, and wherein the rod contains an electrode operatively connected to the magnetorheological piston.

6. A magnetorheological damper comprising:

a) an inner tube;

Sub
A1

506
AI

Sub
A2

Sub
A3

12. The magnetorheological damper of claim 10, also including a rod having a first end attached to the magnetorheological piston and having a second end extending outside the inner and outer tubes, wherein the second end

of the inner tube is disposed between the first end of the inner tube and the
5 second end of the rod, and wherein the rod contains an electrode operatively
connected to the magnetorheological piston.

Sub
AY

13. The magnetorheological damper of claim 10, also including
a valve disposed proximate the first end of the inner tube and providing the fluid
communication of the outer tube with the inner tube.

14. The magnetorheological damper of claim 13, wherein the
valve is a pressure and flow control valve.

15. The magnetorheological damper of claim 14, wherein the
valve includes first and second discs, a valve body having at least one orifice,
and a spring, wherein the valve body is disposed between the first and second
discs, wherein the second disc is disposed between the valve body and the
5 spring, and wherein the spring is disposed between the second disc and the
magnetorheological piston.

Add
cl